

# GALAXY

## AG RADIAL R-1W

The Galaxy Ag Radial R-1W features a highly versatile multi-angle design. Steep angle at the centre of the lug provides long tread wear, exceptional mud clearing capability and smooth roading. Shallow angle at the shoulder delivers superior traction and improved hillside stability. In addition, the Galaxy Ag Radial features "pads" between the lugs which act as mud breakers for improved self-cleaning.

Le Galaxy Ag Radial R1 présente un motif de semelle à angles multiples très polyvalent. Les angles prononcés au centre des barrettes assurent une longue durée de vie de la semelle, une capacité d'évacuation de la boue exceptionnelle et une douceur de roulement sur route. Les angles peu profonds à l'épaulement fournissent une traction supérieure et une stabilité accrue sur les terrains en pente. De plus, le Galaxy Ag Radial est muni de « coussinets » entre les barrettes, qui agissent comme des casseurs de boue, générant un autonettoyage amélioré.

**APPLICATIONS**

- Farm Tractors

**UTILISATIONS**

- Tracteurs agricoles



TIRE SIZE	TT/TL	L.I. / S.S.	RIM	O.D.	S.W.	SLR	R.C.	L.C.C.	A.P.	SP.	T.D.
			in	in	in	in	in±2%	lbs	psi	mph	32nds
440/65R24	TL	128A8/125B	14.00	46.9	17.2	20.9	140.0	3960	23	25	57
480/65R24	TL	133A8/130B	15.00	48.2	18.5	21.3	143.8	4532	23	25	58
540/65R24	TL	140A8/137B	16.00	51.8	20.7	23.0	154.3	5500	23	25	61
440/65R28	TL	131A8/128B	14.00	50.7	17.3	22.8	152.0	4290	23	25	57
480/65R28	TL	136A8/133B	15.00	52.6	18.3	23.3	157.6	4928	23	25	58
540/65R28	TL	142A8/139B	16.00	56.1	20.8	24.8	167.6	5830	23	25	60
600/65R28	TL	147A8/144B	18.00	57.5	23.3	25.7	171.8	6765	23	25	62
540/65R30	TL	143A8/140B	16.00	58.1	20.5	25.7	174.1	5995	23	25	61
540/65R34	TL	145A8/142B	16.00	62.2	21.2	28.2	186.9	6380	23	25	61
600/65R34	TL	151A8/148B	18.00	65.6	23.9	29.5	196.5	7590	23	25	62
540/65R38	TL	147A8/144B	16.00	66.2	21.2	29.9	199.1	6765	23	25	61
600/65R38	TL	153A8/150B	18.00	69.6	23.8	31.3	209.1	8030	23	25	62
650/65R38	TL	157A8/154B	20.00	71.3	25.7	32.1	214.1	9075	23	25	64
650/65R42	TL	158A8/155B	20.00	75.6	25.6	34.1	227.4	9350	23	25	64
800/65R32	TL	172A8/169B	25.00	72.2	31.4	32.3	215.0	13860	35	25	72
750/65R26(28LR26)*	TL	158A8/155B	25.00	63.0	30.0	28.0	187.4	9350	23	25	58
750/65R26(28LR26)*	TL	166A8/163B	25.00	63.0	30.0	28.0	187.4	11684	23	25	58d
360/70R24	TL	122A8/119B	11.00	44.7	13.9	20.4	133.8	3300	23	25	53
360/70R28	TL	125A8/125B	11.00	49.5	14.0	22.3	148.7	3630	23	25	53
380/70R24	TL	125A8/122B	12.00	47.2	15.1	21.0	140.7	3630	23	25	53
420/70R24	TL	130A8/127B	13.00	48.5	16.8	22.2	144.7	4180	23	25	57

\* R-1 Tread Pattern

Tire Size	TT/TL	L.I. / S.S.	RIM	O.D.	S.W.	SLR	R.C.	L.C.C.	A.P.	SP.	T.D.
			in	in	in	in	in±2%	lbs	psi	mph	32nds
380/70R28	TL	127A8/124B	12.00	51.3	15.0	23.2	153.7	3850	23	25	53
420/70R28	TL	133A8/130B	13.00	53.1	16.3	23.5	159.2	4532	23	25	57
480/70R28	TL	140A8/137B	15.00	56.3	18.8	25.3	168.5	5500	23	25	59
480/70R30	TL	141A8/138B	15.00	57.6	18.9	25.7	172.5	5665	23	25	59
480/70R34	TL	143A8/140B	15.00	61.9	19.2	28.3	185.7	5995	23	25	59
520/70R34	TL	148A8/145B	16.00	64.5	20.9	29.1	193.5	6930	23	25	60
520/70R38	TL	150A8/147B	16.00	68.6	20.8	31.0	206.2	7370	23	25	61
580/70R38	TL	155A8/152B	18.00	72.9	22.8	31.9	215.2	8525	23	25	64
580/70R38	TL	170A8/167B	18.00	72.9	22.8	31.9	215.2	8525	23	25	64
620/70R42	TL	160A8/157B	20.00	75.5	24.6	33.1	226.9	9900	23	25	66
710/70R38	TL	166A8/163B	23.00	76.8	29.2	34.0	229.8	11660	23	25	73
710/70R42	TL	173A8/170B	23.00	81.9	29.3	36.9	245.4	14300	35	25	73
280/85R20	TL	112A8/109B	10.00	38.8	11.1	17.6	115.9	2292	23	25	52
280/85R24(11.2R24)	TL	115A8/112B	10.00	42.5	11.2	19.4	127.5	2486	23	25	52
320/85R24(12.4R24)	TL	122A8/191B	11.00	44.7	12.7	20.6	133.9	3069	23	25	54
340/85R24(13.6R24)	TL	125A8/122B	12.00	46.9	14.1	21.5	140.1	3376	23	25	57
380/85R24(14.9R24)	TL	131A8/128B	12.00	50.1	15.0	22.3	149.4	3990	23	25	59
420/85R24(16.9R24)	TL	137A8/134B	15.00	52.0	17.7	23.3	154.9	4706	23	25	60
280/85R28(11.2R28)	TL	118A8/115B	10.00	46.5	11.1	21.3	140.0	2701	23	25	52
320/85R28(12.4R28)	TL	124A8/121B	11.00	49.5	12.6	22.6	148.7	3274	23	25	54
340/85R28(13.6R28)	TL	127A8/124B	12.00	51.5	13.9	23.5	154.4	3581	23	25	57
380/85R28(14.9R28)	TL	133A8/130B	12.00	54.3	14.9	24.7	162.4	4215	23	25	59
420/85R28(16.9R28)	TL	139A8/136B	15.00	56.6	17.8	25.1	169.2	4972	23	25	60
380/85R30(14.9R30)	TL	135A8/132B	12.00	55.4	14.9	25.2	166.1	4461	23	25	59
420/85R30(16.9R30)	TL	140A8/137B	15.00	58.4	18.0	26.5	174.8	5116	23	25	60
460/85R30(18.4R30)	TL	145A8/142B	16.00	60.1	19.2	26.8	179.8	5934	23	25	63
380/85R34(14.9R34)	TL	137A8/137B	12.00	58.5	15.3	26.8	176.0	4706	23	25	59
420/85R34(16.9R34)	TL	142A8/139B	15.00	62.8	17.3	28.0	188.3	5422	23	25	60
460/85R34(18.4R34)	TL	147A8/144B	16.00	64.9	19.3	29.3	194.6	6292	23	25	63
420/85R38(16.9R38)	TL	144A8/141B	15.00	65.6	17.6	29.6	197.4	5729	23	25	60
460/85R38 480/80R38 (18.4R38)	TL	149A8/146B	16.00	68.4	19.0	30.6	205.0	6650	23	25	63
520/85R38(20.8R38)	TL	155A8/152B	16.00	73.3	20.7	33.1	220.0	7929	23	25	64
460/85R42 480/80R42 (18.4R42)	TL	150A8/147B	16.00	73.4	19.4	33.2	220.9	6855	23	25	63
520/85R42(20.8R42)	TL	157A8/154B	16.00	77.1	21.3	34.4	231.7	8441	23	25	64
520/85R42(20.8R42)	TL	162A8/159B	16.00	77.1	21.3	34.4	231.7	8441	23	25	64
480/80R46(18.4R46)	TL	158A8/155B	16.00	77.6	19.3	35.6	233.7	8696	35	25	63
520/85R46(20.8R46)	TL	158A8/155B	16.00	81.2	21.3	36.3	244.4	8696	23	25	64
380/90R46(14.9R46)	TL	149A8/146B	12.00	73.5	15.4	34.2	221.8	6650	35	25	59
420/90R30(16.9R30)	TL	142A8/139B	13.00	58.9	17.1	26.7	176.3	5422	23	25	63
620/75R26(23.1R26)	TL	166A8/163B	20.00	63.2	25.3	28.4	188.1	10845	46	25	57
500/70R24 *	TL	164A8/164B	17.00	51.8	19.9	23.0	152.6	11020	58	25	45

\* Galaxy Backtrack Radial R-4 design