

**GALAXY****YARDMASTER ULTRA**

Dynamic Tire has successfully proven itself in the market by outperforming on industrial equipment around the globe. Proprietary compounds that offer excellent tread wear characteristics in a variety of conditions, reinforcement that resists unexpected impacts, cuts and abrasions and rim guards that repel foreign objects are what makes Dynamic Tire a leader in material handling.

Dynamic Tire s'est démarquée sur le marché en se surpassant sur des équipements industriels partout sur la planète. Des composés exclusifs qui offrent un excellent coefficient d'usure de la semelle dans diverses conditions, un renforcement qui résiste aux impacts imprévus, aux coupures et aux éraflures, et des protecteurs de jante qui fait fi des corps étrangers, voilà ce qui fait de Dynamic Tire un chef de file dans le domaine de la manutention.

**APPLICATIONS**

- Forklifts

**UTILISATIONS**

- Chariots élévateurs



CODE	SIZE	TYPE	PR	RIM	WT	NS	OD	SW	SLR	L.C.C.@AP	SLR	SP
										lbs@psi		
256826	400-8	TT	8	2.50	11	16	16.6	4.2	7.4	1,150 @ 140	7.4	10
256021	500-8	TT	10	3.00	16	18	18.4	5.4	8.2	1,655 @ 145	8.2	10
256039	600-9	TT	10	4.00	23	20	21.4	6.5	9.5	3,715 @ 125	9.5	10
256050	650-10	TT	12	5.00	31	23	23.7	7.2	10.5	4,740 @ 140	10.5	10
256079	700-12	TT	12	5.00	44	23	26.9	7.9	11.9	5,995 @ 125	11.9	10
256178	250-15	TT	16	7.50	68	25	29.1	9.7	13.1	9,450 @ 135	13.1	10
256802	300-15	TT	20	8.00	108	30	33.3	11.8	14.8	14,500 @ 135	14.8	10
256121	700-15	TT	12	6.00	55	25	30.2	8.4	13.5	6,940 @ 125	13.5	10
256127	750-15	TT	12	6.00	64	25	31.8	8.7	14.3	7,690 @ 115	14.3	10
256134	28X9-15	TT	14	7.00	55	24	27.9	8.4	12.7	7,530 @ 140	12.7	10
256137	825-15	TT	14	6.50	77	25	33.6	9.6	14.9	9,385 @ 120	14.9	10
256210	750-16	TT	16	6.00	68	38	32.9	8.8	14.8	6,405 @ 150	14.8	5
256313	900-20	TT	14	7.00	135	38	40.8	10.6	18.3	8,550 @ 102	18.3	5
256322	1000-20	TT	16	7.50	156	43	42.3	11.2	18.8	14,910 @ 115	18.8	10
256336	1200-20	TT	20	8.50	211	48	45.3	12.6	20.1	19,940 @ 130	20.1	10